

Technische informatie



- **Materiaal:** Rubber type SBR
- **Techniek :** vulcanisatie
- **Lengte :** 150 > 2750 mm
- **Diameter max :** 60 > 2000 mm
- **Gas :** à l'air
- **Temperatuur:** -20 à +60°C
- **werkdruk :** max 3 bar
- **Options :** thermische bescherming

Ref.	Balg onder druk min Ø (mm)	Balg onder druk maxi Ø (mm)	Balg leeg Ø (mm)	Lengte (mm)	Werkdruk (bar)	Gewicht(kg)	Ankers
OPL 30/60	30	60	29	150	3	0.2	NA
OPL 45/80	45	80	43	150	3	0.3	NA
OPL 50/100	50	100	45	110	3	0.3	NA
OPL 65/125	65	125	63	250	3	0.4	NA
OPLS 75/150	75	150	70	195	3	0.5	NA
OPL 75/150	75	150	70	350	3	0.8	NA
OPLS 100/200	100	200	90	250	3	0.8	NA
OPL 100/200	100	200	86	350	3	1.3	NA
OPL 100/150	100	150	90	125	3	0.6	NA
OPL 100/250	100	250	86	600	3	2.2	NA
OPL 125/200	125	200	110	152	3	0.7	NA
OPL 150/250	150	250	145	255	3	2	1xM8
OPL 150/300	150	250	145	255	3	2.6	1xM8
OPL 200/400	200	400	190	555	3	5.5	2xM10
OPL 300/500	300	500	170	725	3	5.5	1xM8
OPL 300/600	300	600	288	715	3	12	2xM10
OPL 300/800	300	800	275	1200	3	18	2xM10
OPL 400/800	400	800	370	1030	3	22	2xM12
OPL 500/1000	500	1000	472	1140	3	32.5	2xM12
OPL 500/1400	500	1400	490	2200	1.5	55	2xM12
OPL 600/1200	600	1200	570	1400	1.5	49	2xM16
OPL 600/1500	600	1500	570	2180	1.5	65	3xM16
OPL 800/1600	800	1600	770	2000	1.5	90	3xM16
OPL 800/2000	800	2000	760	2750	1.5	125	4xM16