



The storm-drain sealing set is used to quickly seal roadside storm-drains in the event of chemical spill and to keep contaminants out of drainage system. Used as a standard equipment by first response units.

Quick inflation

Easy positioning

High resistance to chemicals

Used by first response units

GULLY SET 100-150

PART NUMBER	DESCRIPTION	QUANTITY [pc]
528571	Gully plug 100-150 2.5 bar with inflation hose 2.5 m and rope 2.5 m	4
528875	Foot pump with safety valve 2.5 bar	1
528744	Positioning rod, 1.5 m 3-part	1
528871	Portable case 609 x 409 x 140 Type 2	1

PORTABLE CASE
528871

GULLY PLUG 100-150 2.5 BAR
WITH INFLATION HOSE 2.5 m
AND ROPE 2.5 m
528571

FOOT PUMP
528875

POSITIONING ROD
528744

PART NUMBER	DESCRIPTION	QUANTITY [pc]
528157	Gully plug 300-500 0.5 bar with inflation hose 2 m and rope 2 m	1
529385	Inflation and safety device with finger-tight connector, pressure reducer, safety valve 0.5 bar, pressure gauge and safety coupling	1
523002	Compressed air cylinder 200 bar, 1 l	1
528871	Portable case 609 x 409 x 140 Type 2	1

GULLY SET 300-500



TECHNICAL DATA

TYPE	PART NUMBER	SIZE USAGE RANGE		WEIGHT	WORKING PRESSURE	DEFLATED PLUG DIMENSIONS		RUBBER BODY	INFLATION VALVE
		MIN. DIAMETER	MAX. DIAMETER			DIAMETER	LENGTH	LENGTH	Thread size
		[mm]	[mm]			[mm]	[mm]	[mm]	
GULLY 100-150	528571	100	150	0.5	2.5	86	200	165	R 1/4"
GULLY 300-500	528157	300	500	3.8	0.5	274	385	350	R 1/4"