



The pipe plug kit consists of oil-resistant plugs with electrostatic and spark resistant accessories. It is used by first response units for sealing pipes of different sizes or other round holes in tanks, barrels, etc.

**Oil-resistant
plugs**

**Electrostatic and
spark protected parts**

**Corrosion-resistant
parts**

**Used by first
response units**

PIPE PLUG KIT



THE PIPE PLUG KIT CONSISTS OF:

PART NUMBER	DESCRIPTION	QUANTITY [pc]
542488	Elliptical Plugy G1 50-80 C	1
542489	Elliptical Plugy G2 80-130 C	1
542490	Elliptical Plugy G3 100-160 C	1
523289	Pneumatic plug type Z1 C	1
523290	Pneumatic plug type Z1 1/2 C	1
523292	Pneumatic plug type Z2/3 C	1
523294	Pneumatic plug type Z3/4 C	1
523296	Pneumatic plug type Z4/6 C	1
523302	Pneumatic plug type S2 C	1
523304	Pneumatic plug type S3/4 C	1
523307	Pneumatic plug type S4/6 C	1
541951	Tyre valve extension hose 1 m	2
551285	Inflation hose 3 m, antistatic	1
541957	Static discharge kit	1
541960	Hand pump - mini	1
541952	Shut-off valve R 1/8"	1
541953	Shut-off valve R 1/2"	1
541958	Bag of corks	1
542217	Portable case 609 x 409 x 140 type 3 (with foam)	1

TECHNICAL DATA

TYPE	PART NUMBER	SIZE USAGE RANGE		WEIGHT	WORKING PRESSURE	DEFLATED PLUG DIMENSIONS		INFLATION VALVE	BYPASS DIAMETER
		MIN. DIAMETER	MAX. DIAMETER			DIAMETER	RUBBER BODY LENGTH		
		[mm]	[mm]			[mm]	[mm]		
ELLIPTICAL PLUGY G1 50-80 C	542488	45	80	0.3	3	45	280	R 1/4"	/
ELLIPTICAL PLUGY G2 80-130 C	542489	75	130	0.4	2.5	76	360	R 1/4"	/
ELLIPTICAL PLUGY G3 100-160 C	542490	100	160	0.6	2	98	420	R 3/8"	/
PNEUMATIC PLUG TYPE Z1 C	523289	20	30	0.01	2.5	19	65	R 1/8"	/
PNEUMATIC PLUG TYPE Z1 1/2 C	523290	33	40	0.1	2.5	32	70	R 1/4"	/
PNEUMATIC PLUG TYPE Z2/3 C	523292	50	75	0.1	2.5	45	80	R 1/4"	/
PNEUMATIC PLUG TYPE Z3/4 C	523294	75	100	0.3	2.5	70	100	R 1/4"	/
PNEUMATIC PLUG TYPE Z4/6 C	523296	100	150	0.5	2.5	85	165	R 1/4"	/
PNEUMATIC PLUG TYPE S2 C	523302	50		0.2	2.5	45	80	R 1/8"	1/8"
PNEUMATIC PLUG TYPE S3/4 C	523304	75	100	0.4	2.5	70	100	R 1/8"	1/2"
PNEUMATIC PLUG TYPE S4/6 C	523307	100	150	0.7	2.5	85	165	R 1/8"	1/2"