



TYPE 26

CHEMICAL-RESISTANT PLUGS MADE FROM CR RUBBER – PLUGY C AND PLUGSY C

1. 8.



Savatech PLUGY C and PLUGSY C are made from special CR rubber compound and are reinforced with aramid cord. Owing to their superb resistance to certain chemicals, they are ideal for use in the oil and gas industry.

Available in different sizes

Superb resistance to various liquids

Specially developed for use in refineries and food processing companies


CR rubber compound



ACCESSORIES



SINGLE FITTING CONTROLLER,
0.9 KG
2.5 BAR 60310
1.5 BAR 74609
1.0 BAR 74653



HAND HELD SINGLE
DEADMAN 2.5 BAR,
0.9 KG
519442



INFLATION HOSE,
10 M, BLUE,
1.2 KG
71248



INFLATION HOSE,
10 M, YELLOW,
1.2 KG
76686



INFLATION HOSE,
10 M, RED,
1.2 KG
74268



POLY LIFT INFLATION
HOSE,
5 M, 1.9 KG 60957
10 M, 2.4 KG 60958

1. 8.

CHEMICAL-RESISTANT PLUGS MADE FROM CR RUBBER – PLUGY C AND PLUGSY C

PLUGY C - BLOCKING PLUGS

PART NUMBER	NOMINAL SIZE	SIZE USAGE RANGE		REQUIRED INFLATION PRESSURE (BAR)	DEFLATED PLUG		PRODUCT WEIGHT (KG)	EYE BOLT	INFLATION VALVE
		MIN. DIA. (MM)	MAX. DIA. (MM)		DIAMETER (MM)	RUBBER LENGTH (MM)			
526621	40-70	40	70	2.5	35	160	0.2	NA	R 1/4"
526622	70-150	70	150	2.5	68	300	0.4	NA	R 1/4"
60506	100-200	100	200	2.5	92	500	1.35	M6	R 1/4"
60507	150-300	150	300	2.5	142	540	2.6	M8	R 1/4"
60510	200-400	200	400	2.5	192	600	3.6	M8	R 1/4"
526623	300-525	300	525	2.5	272	630	6.8	M8	R 1/4"
60511	350-600	350	600	2.5	322	830	9.8	M10	R 1/4"
526624	375-750	375	750	2.5	342	1050	11.9	M10	R 1/4"
526625	500-800	500	800	2.5	472	1150	19.5	M10	R 1/4"
510070	500-1000	500	1000	1.5	472	1150	19.5	M10	R 1/4"
526626	600-1200	600	1200	1.5	574	1450	38	M10	2 x R 3/8"
528252	750-1500	750	1500	1	600	2300	75	M10	2 x R 1/4"
563299	800-1800	800	1800	1	600	3000	106	M10	2 x R 1/4"

PLUGSY C - BYPASS PLUGS

PART NUMBER	NOMINAL SIZE	SIZE USAGE RANGE		REQUIRED INFLATION PRESSURE (BAR)	DEFLATED PLUG		PRODUCT WEIGHT (KG)	EYE BOLT	INFLATION VALVE	BYPASS DIAMETER (FEMALE)
		MIN. DIA. (MM)	MAX. DIA. (MM)		DIAMETER (MM)	RUBBER LENGTH (MM)				
526637	100-200	100	200	2.5	92	500	2.7	M6	R 1/4"	1"
526636	150-300	150	300	2.5	142	540	4.3	M8	R 1/4"	1"
526635	200-400	200	400	2.5	192	600	7	M8	R 1/4"	2"
526634	300-525	300	525	2.5	272	630	12	M8	R 1/4"	2"
526633	350-600	350	600	2.5	322	830	16	M10	R 1/4"	2"
526631	375-750	375	750	2.5	342	1050	19.7	M10	R 1/4"	2"
526629	500-800	500	800	2.5	472	1150	32.5	M10	R 1/4"	2"
526628	500-1000	500	1000	1.5	472	1150	32.5	M10	R 1/4"	2"
526627	600-1200	600	1200	1.5	574	1450	55.5	M10	2 x R 3/8"	4"
529446	750-1500	750	1500	1	600	2300	91	M10	2 x R 1/2"	4"
581132	800-1800	800	1800	1	600	3000	117	M10	2 x R 1/2"	4"

BACK PRESSURES (bar)* - PLUGY C, PLUGSY C

PLUG SIZE	PIPE DIAMETER (MM)																			
	40	70	100	150	200	250	300	350	400	500	600	800	1000	1200	1300	1400	1500	1600	1700	1800
40-70	2	1.2																		
70-150		2.2	1.7	1.3																
100-200			2.2	1.7	1.3															
150-200				2	1.5															
150-300				2.2	2	1.4	1.2													
200-400					2.2	2	1.7	1.5	1.2											
300-525							2	1.7	1.5	1.2										
350-600								2.1	1.9	1.6	1.3									
375-750									2	1.7	1.4									
500-800										1.8	1.4	1.1								
500-1000										1	0.8	0.6	0.5							
600-1200											1	0.7	0.6	0.5						
750-1500												1	0.9	0.8	0.7	0.6	0.5			
800-1800												1	1	0.9	0.8	0.7	0.6	0.5	0.5	0.4

* measured in a dry iron pipe