



GEKA

CONE-SHAPED PLUGS – PLUGY CP

1. 10.



Savatech CONE PLUGY CP plugs are available in dimensions from 400 mm - 2400 mm. They are produced from special CR rubber and reinforced with fabric. The additional sealing foam improves sealing in all conditions. Plugs are equipped with carrying handles and eyelets for easier manipulation. They are very light and suitable for sealing pipes of various shapes (cone, oval, etc.).

Repairable material

Wide range

Conical shape

Light-weight



Manipulation handles

CONE PLUGY CP – BLOCKING PLUGS

PART NUMBER	NOMINAL SIZE	SIZE USAGE RANGE		REQUIRED INFLATION PRESSURE (BAR)	INFLATED PLUG		BACK PRESSURE* (BAR)	INFLATION VALVE
		MIN. DIA. (MM)	MAX. DIA. (MM)		WEIGHT (KG)	LENGTH (MM)		THREAD SIZE
574340	400-1000	400	1000	1	16.6	2000	0.5	R1/2"
574341	600-1500	600	1500	1	35.7	3000	0.5	R1/2"
574342	700-2000	700	2000	1	83.8	3600	0.5	R1/2"
574343	900-2400	900	2400	1	111.5	4800	0.5	R1/2"

* back pressure 0.5 bar water or 0.2 bar air/vacuum

ACCESSORIES



DOUBLE FITTING CONTROLLER, 2.0 KG
504061



INFLATION HOSE 10 M WITH SAFETY GEKA COUPLING, 3.0 KG
519817