



Savatech multi-size plugs with a larger bypass PLUGSY VP cover the ranges from 100 mm up to 1800 mm. A replaceable rubber sleeve is reinforced with aramid cord and ensures safe and simple handling. Plugs are available in three different designs, depending on the conditions and bypass requirements.



Bypass diameter
up to 8 inches

Replaceable rubber
sleeve and bypass flange

Non-corrosive
metal parts



VP2
PLUGSY VP 200-400 4"
60968



VP2
BYPASS ADAPTER
R2" FOR PLUGSY 200-400
520344

ACCESSORIES



SINGLE FITTING CONTROLLER,
0.9 KG
2.5 BAR 60310
2.0 BAR 565643
1.5 BAR 74609
1.0 BAR 74653



INFLATION HOSE,
10 M, RED, 1.2 KG
74268



INFLATION HOSE,
10 M, BLUE, 1.2 KG
71248



INFLATION HOSE,
10 M, YELLOW, 1.2 KG
76686



POLY LIFT INFLATION
HOSE, 5 M, 1.9 KG
60957



POLY LIFT INFLATION
HOSE, 10 M, 2.4 KG
60958

PLUGSY VP - BYPASS PLUG

PART NUMBER	NOMINAL SIZE	SIZE USAGE RANGE		REQUIRED INFLATION PRESSURE (BAR)	DEFLATED PLUG		PRODUCT WEIGHT (KG)	EYE BOLT M THREAD	INFLATION VALVE THREAD SIZE	BYPASS DIAMETER (FEMALE)
		MIN. DIA. (MM)	MAX. DIA. (MM)		DIAMETER (MM)	RUBBER LENGTH (MM)				
516942	100-150	98	150	2.5	88	370	2.2	M 6	Not removable	2"
516943	150-250	148	250	2	136	520	4.6	M 6	Not removable	3" (2")
520334	Bypass adapter R2" for PLUGSY 150-250 VP1									
516944	200-300	198	300	2	186	550	7.6	M 6	Not removable	4" (2")
520341	Bypass adapter R2" for PLUGSY 200-300 VP1									
60967	150-300	150	300	1.5	142	540	3.6	M 8	-	2"
514953	Bypass adapter R2" for PLUGSY 150-300 VP2									
60968	200-400	200	400	1.5	192	600	6.1	M 8	-	4" (2")
520344	Bypass adapter R2" for PLUGSY 200-400 VP2									
514954	Bypass adapter R4" for PLUGSY 200-400 VP2									
533539	300-525	300	525	1.5	272	630	11.7	M 10	R 1/4"	6" (4", 2")
534617	By pass adapter R4" for PLUGSY 300-525 VP2									
534615	By pass adapter R6" for PLUGSY 300-525 VP2									
60970	350-600	350	600	1.5	322	830	17	M 10	R 1/4"	6" (4", 2")
520347	Bypass adapter R4" for PLUGSY 350-600 VP2									
514955	Bypass adapter R6" for PLUGSY 350-600 VP2									
60971	500-1000	500	1000	1.5	472	1150	37.5	M 10	R 1/4"	8" (6", 4", 2")
520349	Bypass adapter R4" for PLUGSY 500-1000 VP2									
520348	Bypass adapter R6" for PLUGSY 500-1000 VP2									
514956	Bypass adapter R8" for PLUGSY 500-1000 VP2									
535873	600-1200	600	1200	1.5	574	1450	65.1	M 12	2 x R 3/8"	6"
535874	600-1200	600	1200	1.5	574	1450	70.5	M 12	2 x R 3/8"	8"
535876	750-1500	750	1500	1	600	2300	79	M 12	2 x R 1/2"	6"
535878	750-1500	750	1500	1	600	2300	83	M 12	2 x R 1/2"	8"
535879	800-1800	800	1800	1	800	3000	121	M 12	2 x R 1/2"	6"
535880	800-1800	800	1800	1	800	3000	125	M 12	2 x R 1/2"	8"

VP1 VP1 Plugs are supplied with a thread, a bypass adapter needed only if reducing the bypass size

VP2 VP2 Plugs are supplied without a thread, therefore a bypass adapter is always required to ensure full functionality, it is sold separately in different sizes

VP3 VP3 Plugs are supplied with a built-in adapter, which is included in plug's price



BACK PRESSURES (bar)* - PLUGSY VP

PLUG SIZE	PIPE DIAMETER (MM)												
	100	150	200	250	300	350	400	500	600	700	800	900	1000
100-150	1	0.8											
150-250		1	0.8	0.6									
200-300			1	0.8	0.6								
150-300		1	0.8	0.7	0.6								
200-400			1.1	0.9	0.7	0.6	0.6						
300-525					1	0.9	0.7	0.5					
350-600						0.9	0.8	0.7	0.6				
500-1000								1.1	0.9	0.8	0.7	0.6	0.6

BACK PRESSURES(bar)* - PLUGSY VP

PLUG SIZE	PIPE DIAMETER (MM)									
	600	800	1000	1200	1300	1400	1500	1600	1700	1800
600-1200	1	0.8	0.6	0.5						
750-1500		1	0.9	0.7	0.6	0.5	0.4			
800-1800		1	1	0.8	0.8	0.7	0.6	0.5	0.4	0.4

* measured in a dry iron pipe